## FORD TRUCKS 4142M EURO6

Basic Features Vehicle Type	Mixer			
Axle	8x4			
Emission	Euro 6			
Cabin Type	Day Cab			
Wheelbase (mm)	5100			
Engine	5100			
Туре	Ecotorg 12,7 liters			
Displacement (cc)	12740			
Bore x Stroke	130 mm x 160 mm			
Power	420 PS (308,9 kW ) / 1800 rpm			
Torque	2150 Nm / 1000-1300 rpm			
Compression Ratio	17 +/- 0.5 : 1			
Oil Filling Volume	50 L			
Coolant Volume	57 L (77 L with Intarder)			
Transmission				
Clutch	430 mm Single Disc			
Manuel Transmission / Ratios (1. gear - 16. gear)	ZF 16S 2530 (13,805-0,836)			
Automated Transmission / Ratios (1. gear - 16. gear)	Ecotorg 16S 2600 OD AMT (14,107 – 0,823)			
Steering				
	Electro-Hydraulic Power-Assisted Steering System (EHPAS)			
Chassis				
Chassis Thickness	10 mm with Local Reinforcement			
	500 MPa			
Chassis Strength	500 MPa			
	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension			
Suspension (Front / Rear)				
Suspension (Front / Rear) Axle	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension			
Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic)	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction			
Chassis Strength Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic) Tyres Wheel Rim	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 / 3,57			
Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic) Tyres	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 / 3,57 315/80 R 22,5			
Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic) Tyres Wheel Rim	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 / 3,57 315/80 R 22,5			
Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic) Tyres Wheel Rim <b>Braking System</b>	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 / 3,57 315/80 R 22,5 22,5 x 9 Steel			
Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic) Tyres Wheel Rim Braking System Brakes (Ømm x mm Length)	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 / 3,57 315/80 R 22,5 22,5 x 9 Steel 430 x 45 - Disc Brakes			
Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic) Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System Engine Brake Power	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 / 3,57 315/80 R 22,5 22,5 x 9 Steel 430 x 45 - Disc Brakes Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater			
Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic) Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System Engine Brake Power Intarder Power	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 / 3,57 315/80 R 22,5 22,5 x 9 Steel 430 x 45 - Disc Brakes Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level)			
Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic) Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 / 3,57 315/80 R 22,5 22,5 x 9 Steel 430 x 45 - Disc Brakes Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level)			
Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic) Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System Engine Brake Power Intarder Power Electrical System Battery	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 / 3,57 315/80 R 22,5 22,5 x 9 Steel 430 x 45 - Disc Brakes Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level) max. 450 kW / continuous 160 kW			
Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic) Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System Engine Brake Power Intarder Power Electrical System Battery Alternator / Starter Motor	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 / 3,57 315/80 R 22,5 22,5 x 9 Steel 430 x 45 - Disc Brakes Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level) max. 450 kW / continuous 160 kW			
Suspension (Front / Rear) Axle Axle Ratio (Manual / Automatic) Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System Engine Brake Power Intarder Power Electrical System	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 / 3,57 315/80 R 22,5 22,5 x 9 Steel 430 x 45 - Disc Brakes Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level) max. 450 kW / continuous 160 kW			



Dimensions (mm)					
Front Overhang			1500		
Wheelbase			5100		
Overall Length			8890		
Distance Between 1st and 2nd Wheel Centers			2050		
Distance Between 2 <sup>nd</sup> and 3 <sup>th</sup> Wheel Centers			3050		
Distance Between 3 <sup>th</sup> and 4 <sup>th</sup> Wheel Centers			1350		
Overall Cab Length			1820		
Overall Vehicle Height			3200		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			940		
Useful Chassis Length			6494		
Chassis Height - Front			1185		
Chassis Height - Rear			1186		
Ground Clearance - Front			380		
Ground Clearance - Rear			296		
Turning Radius			10640		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	8000	8000	13400	13400	41900
Kerb Weight	3676	3848	1913	1913	11350
Payload	4354	4152	11487	11487	30550
GVM (Legal)	8000	8000	9500	9500	32000

## STANDARD EQUIPMENT

- Manuel Air conditioner
- Multimedia System with 9'' Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- 4 Points Independent Cab Suspension for Day Cab
- Engine Driven PTO & Interior Control Unit
- Cruise Control
- Engine Brake
- Disc Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Anti-lock Brake System (ABS)
- Continuous Wear Sensor
- Immobilizer
- Home Safe
- Approach Lights
- Differential Lock
- Digital Tachograph
- Rear Window \*\*
- Front Towing Hooks (Double Hook)
- Short Bumper
- DAB Radio\*\*\*
- Electronic Brake System (EBS) and Electronic Stability Control (ESP)
- Automatic Traction Control (ATC)
- Advanced Driver-Assistance Systems (Cybersecurity Improvements, Rear View Camera, Moving-off Information System, Blind Spot Information System, Tire Pressure Monitoring System, Emergency Stop Signal, Alcohol Interlock Facilitation, Traffic Sign Recognition, Driver Alert System, Lane Keeping Alert)

## OPTIONAL EQUIPMENT

- Intarder
- ADR Pack
- Wet Type Cab Heater
- Auxiliary Cabin Heater (Wet Type)
- Cold Pack with Dry & Wet Type Cab Heater and 225 Ah Battery\*
- Switchable Air Compressor for Improved Fuel Economy
- Transmission Driven PTO Options & Interior Control Unit
- Rubber Suspension (28T)\*\*
- Front and Rear Vehicle Antiroll Bars
- Dual Passenger Seat\*
- Lateral Protection
- Manually Operated Sunroof
- Less Spare Tire
- Rear Towing Hook
- Twin PTO (high ratio) / Twin PTO (low ratio)\*\*\*\*

<sup>\*</sup> Not available with Low Roof Sleeper cab version. \*\* 241 kg lighter compared to standard suspension vehicle. \*\*\* DAB Radio can be standard or optional according to the market.

This leaflet includes products designed for Ford vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications provided herein are for standard vehicles. Selection of any optional accessories might cause differences from these specifications.