FORD **TRUCKS** 4442D EURO6

Basic Features					
Vehicle Type	Tipper				
Axle	8x4				
Emission	Euro 6				
Cabin Type	Day Cab				
Wheelbase (mm)	5100				
Engine					
Туре	Ecotorq 12,7 litre				
Displacement (cc)	12740				
Diameter x Stroke	130 mm x 160 mm				
Power	420 PS (308,9 kW) / 1800 rpm				
Torque	2150 Nm / 1000-1300 rpm				
Compression Ratio	17 +/- 0,5 : 1				
Oil Filling Volume	50 L				
Coolant Volume	57 L (77 L with Intarder)				
Transmission					
Clutch	2 x 400 mmTwin Clutch				
Manuel Transmission / Ratios (1. gear - 16. gear)	ZF 16S 2530 (13,805-0,836)				
Automated Transmission / Ratios (1. gear - 16. gear)	Ecotorq 16S 2600 OD (14,107 - 0,823)				
Steering					
	Electro-Hydraulic Power-Assisted Steering System (EHPAS)				
Chassis					
Chassis Thickness	10 mm with Reinforcement				
Chassis Strength	500 MPa				
Suspension (Front / Rear)	90 mm Parabolic Leaf Springs / Reinforced Parabolic Suspension				
Axle	Hub Reduction				
Axle Ratio (Manual / Automatic)	4,87 / 4,08				
Tyres	385/65R 22.5				
Wheel Rim	22,5 x 11,75 Steel				
Braking System					
Brakes (Ø mm x mm Length)	410 x 200, Z-Cam Drum Brake System				
Braking System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater				
Engine Brake Power	max. 320 kW (Engine Level)				
Intarder Power	max. 450 kW / Continuous 160 kW				
Electrical System					
Battery	225 Ah				
Alternator / Starter Motor	130 A / 6,5 kW				
Tanks					
Fuel Tank	315 L Steel				
SCR Tank	55 L				



Dimensions (mm)					
Front Overhang			1485		
Wheelbase			5100		
Overall Length			8883		
Distance Between 1st and 2nd Wheel Centers			2050		
Distance Between 2 nd and 3 th Wheel Centers			3050		
Distance Between 3th and 4th Wheel Centers			1350		
Overall Cab Length			1827		
Total Vehicle Height			3249		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			948		
Useful Chassis Length			6165		
Chassis Height - Front			1184		
Chassis Height - Rear			1193		
Ground Clearance - Front			379		
Ground Clearance - Rear			305		
Turning Radius			10640		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	9000	9000	13400	13400	44000
		0700		2055	

Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	9000	9000	13400	13400	44000
Kerb Weight	3851	3728	2057	2056	11692
Payload	5149	5272	11343	11344	32308
GVM (Legal)	8000	8000	9500	9500	32000

STANDARD EQUIPMENT

- Manuel Air conditioner
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto,
- Remote Control)
- 4 Points Independent Cab Suspension for Day Cab
- Transmission Offset (single gear) PTO without Flange & Interior Control Unit
- Cruise Control
- Drum Brake
- Engine Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Switchable Air Compressor for Improved Fuel Economy
- Lumbar Support
- Anti-Lock Brake System (ABS)
- Brake Lining Wear Indicator
- Immobilizer
- Home Safe Light
- Approach Light
- Differential Lock
- Digital TachographFront Towing Hooks (Double Hook)
- Short Bumper
- DAB Radio***
- Advanced Driver-Assistance Systems (Cybersecurity Improvements, Rear View Camera, Moving-off Information System, Blind Spot Information System, Tire Pressure Monitoring System, Emergency Stop Signal, Alcohol Interlock Facilitation, Traffic Sign Recognition, Driver Alert System, Lane Keeping Alert
- Electronic Brake System (EBS) and Electronic Stability Control (ESP)
- Automatic Traction Control (ATC)

OPTIONAL EQUIPMENT

- Automated Transmission (with Normal Mode, Off-Road Mode, Rocking Mode)
- Engine Driven PTO & Interior Control Unit
- Transmission Driven PTO Options & Interior Control Unit
- Intarder
- Auxiliary Cabin Heater (Wet Type)
- Cold Pack with Wet Type Cab Heater and 225 Ah Battery*
- Power Cab Tilting
- Rear Window **
- 4750 mm Wheelbase Version
- Double Passenger Seat
- Extra Heavy Duty Pack (Available With 13R 22,5 Tyre)
- O2 up to 3,5T towing capability
- O3 up to 10T towing capability
- O4 more than 10T towing capability
- Manually Operated Sunroof
- Front Vehicle Antiroll Bar
- Oil Pan Protection
- Multileaf Spring Front Suspension
- Lateral Protection
- Reinforced Wheel Rim
- Less Spare Tire
- Rear Towing Hook Option
- Twin PTO (high ratio) / Twin PTO (low ratio)****

^{*} Not Available with 4750 mm Wheelbase Version.

^{**} Not Available with Low Roof Sleeper Cab Version.

^{***} DAB Radio can be standard or optional according to the market.