FORD TRUCKS 4442P EURO6

Basic Features Vehicle Type	Concrete Pump			
Axle	8x4			
Emission	Euro 6			
Cabin Type	Day Cab			
Wheelbase (mm)	5100			
Engine				
Туре	Ecotorg 12.7 lt			
Displacement (cc)	12740			
Bore x Stroke	130 mm x 160 mm			
Power	420 PS (308,9 kW) / 1800 RPM			
Torque	2150 Nm / 1000-1300 RPM			
Compression Ratio	17+/-0.5:1			
Oil Filling Volume	50 L			
Coolant Volume	57 L			
Transmission				
Clutch	430 mm Single Disc			
Manuel Transmission / Ratios (1. gear - 16. gear)	ZF 16S 2530 (13,805-0,836)			
Steering				
	Electro-Hydraulic Power-Assisted Steering System (EHPAS)			
Chassis				
Chassis Thickness	10 mm with Local Reinforcement			
Chassis Strength	500 MPa			
Suspension (Front / Rear)	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension			
Axle	Hub Reduction			
Axle Ratio	4,08			
Tyres	385/65R 22.5			
Wheel Rim	22,5 x 11,75 Steel			
Braking System				
Diaking System				
	410 x 200, Z-Cam Drum Brake System			
Braking Cystem Braking System				
Brakes (Ø mm x mm Length)	410 x 200, Z-Cam Drum Brake System Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level)			
Brakes (Ø mm x mm Length) Braking System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater			
Brakes (Ø mm x mm Length) Braking System Engine Brake Power	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater			
Brakes (Ømm x mm Length) Braking System Engine Brake Power Electrical System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level)			
Brakes (Ømm x mm Length) Braking System Engine Brake Power Electrical System Battery	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level) 225 Ah			
Brakes (Ømm x mm Length) Braking System Engine Brake Power Electrical System Battery Alternator / Starter Motor	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level) 225 Ah			



Sharing the load

Dimensions (mm)					
Front Overhang			1490		
Wheelbase			5100		
Overall Length			9836		
Distance Between 1 st and 2 nd Wheel Centers			2050		
Distance Between 2 nd and 3 th Wheel Centers			3048		
Distance Between 3 th and 4 th Wheel Centers			1350		
Overall Cab Length			1827		
Total Vehicle Height			3237		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			1900		
Useful Chassis Length			7435		
Chassis Height - Front			1174		
Chassis Height - Rear			1155		
Ground Clearance - Front			376		
Ground Clearance - Rear			302		
Turning Radius			11930		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	9000	9000	13400	13400	44000
Kerb Weight	3894	3900	2090	2090	11973
Payload	5106	5100	11310	11310	32027
GVM (Legal)	8000	8000	9500	9500	32000

STANDARD EQUIPMENT

- Manuel Air Conditioner
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- 4 Points Independent Cab Suspension for Day Cab
- Cruise Control
- Engine Brake
- Drum Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Front and Rear Vehicle Antiroll Bars
- Anti-Lock Brake System (ABS)
- Brake Lining Wear Indicator
- Immobilizer
- Home Safe Light
- Approach Light
- Differential Lock
- Digital Tachograph
- Switchable Air Compressor for Improved Fuel Economy
- Rear Window
- Short Bumper
- Front Towing Hooks (Double Hook)
- DAB Radio*
- Advanced Driver-Assistance Systems (Cybersecurity Improvements, Rear View Camera, Moving-off Information System, Blind Spot Information System, Tire Pressure Monitoring System, Emergency Stop Signal, Alcohol Interlock Facilitation, Traffic Sign Recognition, Driver Alert System, Lane Keeping Alert)
- Electronic Brake System (EBS) and Electronic Stability Control (ESP)
- Automatic Traction Control (ATC)

OPTIONAL EQUIPMENT

- ADR Pack
- Auxiliary Cabin Heater (Wet Type)
- Cold Pack with Wet Type Cab Heater and 225 Ah Battery
- Power Cab Tilting
- Engine Driven PTO & Interior Control Unit
- Dual Passenger Seat
- Lateral Protection
- Manually Operated Sunroof
- Less Spare Tire
- Twin PTO (high ratio) / Twin PTO (low ratio)**

* DAB Radio can be standard or optional according to the market. **Only available with Automated Transmission.

This leaflet includes products designed for Ford vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications provided herein are for standard vehicles. Selection of any optional accessories might cause differences from these specifications.