FORD **TRUCKS** 2533 DC **EURO**6

Axile 6x2 Ernission Euro 6 Cabin Type Day Cab Wheelbase (mm) 4250 Engline Type Ecotor 9 liters Displacement (cc) 8974 Displacement (cc) 15 mm x 144 mm Power 330 PS (243 kW) @ 1655 - 2200 rpm * Torque 1300 Nm @ 1200-1700 rpm Compression Ratio 176:1 Oll Filling Volume 30 L Coolant Volume 46 L Valaximum power can be taken between 1700 - 2200 rpm with vertical exhaust option. Tansmission / Ratios (1, gear - 9, gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1, gear - 9, gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1, gear - 9, gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1, gear - 9, gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1, gear - 9, gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1, gear - 9, gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1, gear - 9, gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1, gear -	Basic Features					
Emission Euro 6 Cabin Type Day Cab Wheelbase (mm) 4250 Englie Ecotor 9 liters Type Ecotor 9 liters Displacement (cc) 8974 Diameter x Stroke 115 mm x 144 mm Power 330 PS (243 kW) & 1655 - 2200 rpm * Torque 1300 Nm @ 1200-1700 rpm Compression Ratio 17.6 : 1 Oll I Filing Volume 30 L Color (and Volume) 46 L Color (and Volume) 46 L Color (and Volume) 430 mm Single Disc Manual Transmission Ration Clutch 430 mm Single Disc Manual Transmission / Ratios (1, gear - 9 gear) 9+1 Speed (9.40 - 0.75) Automated Transmission / Ratios (1, gear - 9 gear) 9+1 Speed (9.48 - 0.75) Steering Power Assisted Single Circuit Chassis Thickness 7 mm with Reinforcement Chassis Strength 355 MPa Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axie Standard Single Reduction Axie	Vehicle Type	Light Road Truck				
Cabin Type Day Cab Wheelbase (mm) 4250 Engine Ecotorq 9 liters Type Ecotorq 9 liters Displacement (cc) 8974 Diameter x Stroke 115 mm x 144 mm Power 330 PS (243 kW) @ 1655 - 2200 rpm * Torque 1300 Nm @ 1200-1700 rpm Compression Ratio 176:1 Oll Filling Volume 30 L Coolant Volume 46 L *Maximum power can be taken between 1700 - 2200 rpm with vertical exhaust option. Transmission / Ratios (1, gear - 9, gear) 430 mm Single Disc Clutch 430 mm Single Disc Manuel Transmission / Ratios (1, gear - 9, gear) 9+1 Speed (9.40 - 0.75) Automated Transmission / Ratios (1, gear - 9 gear) 9+2 Speed (9.40 - 0.75) Automated Transmission / Ratios (1, gear - 9 gear) 9+3 Speed (9.40 - 0.75) Steering Power Assisted Single Circuit Chassis Strength 355 MPa Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axie Axie Ratio 4.63 Axie Ratio 4.63 <th< td=""><td>Axle</td><td>6x2</td></th<>	Axle	6x2				
Wheelbase (mm) 4250 Engine Ecotor 9 liters Displacement (cc) 8974 Displacement (cc) 105 mm Compression (collated (cc) 105 mm Displacement (cc) 430 mm 106 legs (cc) Market (Transmission (Ratio (logen - 9, gear)) 9+1 Speed (9,40 - 0,75) 106 legs (cc) Market (Transmission / Ratios (logen - 9, gear) 9+1 Speed (9,40 - 0,75) 106 legs (cc) Steering Power Assisted Single Circuit 106 legs (cc) 106 legs (cc) 107 legs (c	Emission	Euro 6				
Engine Ecotorq 9 liters Displacement (cc) 8974 Displacement (cc) 8974 Diameter x Stroke 115 mm x 144 mm Power 330 PS (243 kW) @ 1655 - 2200 rpm* Torque 1300 Nm @ 1200-1700 rpm Compression Ratio 176 - 11 Oil Filling Volume 30 L Coolant Volume 46 L * Maximum power can be taken between 1700 - 2200 rpm with vertical exhaust option. *** * Transmission 46 L * Manuel Transmission / Ratios (1, gear - 9, gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1, gear - 9 gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1, gear - 9 gear) 9+1 Speed (9,48 - 0,75) Steering *** ***Chassis Thickness 7 mm with Reinforcement Chassis Strength 355 Ma Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle 4(3) Suspension (Front/Rear) 9 15/80 R 22,5 Wheel Rim 2,25 x 9 Steel Braking System Dual Brake Circuit - Air Processing Unit With Integrated	Cabin Type	Day Cab				
Type Ecotorq 9 liters Displacement (cc) 8974 Displacement (cc) 8974 Displacement (cc) 115 mm 144 mm Power 330 PS (243 kW) @ 1655 - 2200 rpm* Torque 1300 Nm @ 1200-1700 rpm Compression Ratio 17.6 : 1 Oil Filling Volume 30 L Colant Volume 46 L * Maximum power can be taken between 1700 - 2200 rpm with vertical exhaust option. Transmission Transmission Clutch 430 mm Single Disc Manuel Transmission / Ratios (1, gear - 9, gear) 9+1 Speed (9.40 - 0.75) Automated Transmission / Ratios (1, gear - 9 gear) 9+1 Speed (9.40 - 0.75) Steering Power Assisted Single Circuit Chassis Thickness Chassis Strength 355 MPa Suspension (Front/Rear) 9 rabolic Leaf Spring / Compensating Arm Mechanical Suspension Aule Ratio 4,63 Ayryes (Front/Rear) 315/80 R 22.5 Wheel Rim 22,5 x 9 Steel Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engline Brake Power max 225 KM </td <td>Wheelbase (mm)</td> <td colspan="4"></td>	Wheelbase (mm)					
Displacement (cc)	Engine					
Diameter x Stroke 115 mm x 144 mm	Туре	Ecotorg 9 liters				
Power 330 PS (243 kW) @ 1655 - 2200 rpm * Torque 1300 Nm @ 1200-1700 rpm Compression Ratio 17.6 : 1 OIL Filling Volume 30 L Coolant Volume 46 L * Maximum power can be taken between 1700 - 2200 rpm with vertical exhaust option. Transmission Clutch 430 mm Single Disc Manuel Transmission / Ratios (1, gear - 9, gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1, gear - 9 gear) 9+1 Speed (9,48 - 0,75) Steering Power Assisted Single Circuit Chassis Chassis Thickness 7 mm with Reinforcement Chassis Strength 355 MP Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction Axle Ratio 4,63 Tyrges (Front/Rear) 315/80 R 22,5 Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø,mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max. 220 kW (Engine Level) Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium	Displacement (cc)					
Torque 1300 Nm @ 1200-1700 rpm Compression Ratio 17,6 : 1 Dil Filling Volume 30 L Coolant Volume 46 L * Maximum power can be taken between 1700 - 2200 rpm with vertical exhaust option. * Transmission Clutch 430 mm Single Disc Manuel Transmission / Ratios (1. gear - 9. gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1.gear - 9 gear) 9+1 Speed (9,48 - 0,75) **Steering * Power Assisted Single Circuit Chassis Chassis Thickness 7 mm with Reinforcement Chassis Strength 355 MP Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction Axle Ratio 4,63 Tyres (Front/Rear) 315/80 R 22,5 Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (0,mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max 220 kW (Engine Level) Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank	Diameter x Stroke	115 mm x 144 mm				
Compression Ratio 17.6 : 1 OIL Filling Volume 30 L Coolant Volume 46 L * Maximum power can be taken between 1700 - 2200 rpm with vertical exhaust option. 46 L Transmission Clutch 430 mm Single Disc Manuel Transmission / Ratios (1, gear - 9, gear) 9+1 Speed (9.40 - 0.75) Automated Transmission / Ratios (1, gear - 9 gear) 9+1 Speed (9.48 - 0.75) Steering Power Assisted Single Circuit Chassis Steering Chassis Strength Strength 355 MPa Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction Axle Ratio 4,63 Tyres (Front/Rear) 315/80 R 22.5 Wheel Rim 22,5 x 9 Steel Brakes (Front/Rear) (0,mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max. 220 kW (Engine Level) Electrical System<	Power	330 PS (243 kW) @ 1655 - 2200 rpm*				
Dil Filling Volume	Torque	1300 Nm @ 1200-1700 rpm				
Coolant Volume * Maximum power can be taken between 1700 - 2200 rpm with vertical exhaust option. * Transmission Clutch * Manuel Transmission / Ratios (1. gear - 9. gear) Automated Transmission / Ratios (1.gear - 9. gear) Automated Transmission / Ratios (1.gear - 9. gear) * Power Assisted Single Circuit Chassis Chassis Thickness * Tmm with Reinforcement Chassis Strength * Sapsonsion (Front/Rear) * Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle * Standard Single Reduction Axle * Standard Single Reduction Axle * Standard Single Reduction Axle Ratio * 4,63 * Tyres (Front/Rear) * Standard Single Reduction Axle Ratio * 4,63 * Tyres (Front/Rear) * Standard Single Reduction Axle Ratio * 4,63 * Tyres (Front/Rear) * Standard Single Reduction Axle Ratio * 4,63 * 4,63 * 5,70 * 6,70 * 7,70 * 7,70 * 7,70 * 7,70	Compression Ratio	17,6 : 1				
* Maximum power can be taken between 1700 - 2200 rpm with vertical exhaust option. Transmission Clutch 430 mm Single Disc Manuel Transmission / Ratios (1. gear - 9. gear) 9+1 Speed (9.40 - 0.75) Automated Transmission / Ratios (1.gear - 9 gear) 9+1 Speed (9.48 - 0.75) Steering Power Assisted Single Circuit Chassis Chassis Thickness 7 mm with Reinforcement Chassis Strength 355 MPa Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction Axle Ratio 4,63 Tyres (Front/Rear) 315/80 R 22,5 Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max. 220 kW (Engine Level) Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank Fuel Tank 350 L Aluminium	Oil Filling Volume	30 L				
Transmission Clutch 430 mm Single Disc Manuel Transmission / Ratios (1. gear - 9. gear) 9+1 Speed (9.40 - 0.75) Automated Transmission / Ratios (1.gear - 9 gear) 9+1 Speed (9.48 - 0.75) Steering Power Assisted Single Circuit Chassis Chassis Thickness 7 mm with Reinforcement 355 MPa Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction 4.63 Tyres (Front/Rear) 915/80 R 22.5 Wheel Rim 22.5 x 9 Steel Braking System Brakes (Front/Rear) (0.mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max. 220 kW (Engine Level) Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium	Coolant Volume	46 L				
Clutch 430 mm Single Disc Manuel Transmission / Ratios (1. gear - 9. gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1.gear - 9 gear) 9+1 Speed (9,48 - 0,75) Steering Power Assisted Single Circuit Chassis Chassis Thickness 7 mm with Reinforcement Chassis Strength 355 MPa Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction Axle Ratio 4,63 Tyrges (Front/Rear) 315/80 R 22,5 Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max. 220 kW (Engine Level) Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium	* Maximum power can be taken between 1700 - 2200 rp	om with vertical exhaust option.				
Manuel Transmission / Ratios (1. gear - 9. gear) 9+1 Speed (9,40 - 0,75) Automated Transmission / Ratios (1. gear - 9 gear) 9+1 Speed (9,48 - 0,75) Steering Power Assisted Single Circuit Chassis Chassis Thickness 7 mm with Reinforcement Chassis Strength 355 MPa Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction Axle Standard Single Reduction Axle Ratio 4,63 Tyres (Front/Rear) 315/80 R 22,5 Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max. 220 kW (Engine Level) Electrical System 225 Ah Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks	Transmission					
Automated Transmission / Ratios (1.gear - 9 gear) Steering Power Assisted Single Circuit Chassis Chassis Thickness 7 mm with Reinforcement 355 MPa Suspension (Front/Rear) Axle Axle Axle Axle Axle Axle Axle Axle	Clutch	430 mm Single Disc				
Power Assisted Single Circuit Chassis Chassis Thickness 7 mm with Reinforcement Chassis Strength 355 MPa Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction Axle Atle Standard Single Reduction Axle Akle Standard Single Reduction Axle Acio 4,63 Tyres (Front/Rear) Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) Brakes (F	Manuel Transmission / Ratios (1. gear - 9. gear)	9+1 Speed (9,40 - 0,75)				
Power Assisted Single Circuit Chassis Chassis Thickness 7 mm with Reinforcement Chassis Strength 355 MPa Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction Axle Ratio 4,63 Tyres (Front/Rear) 315/80 R 22,5 Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max. 220 kW (Engine Level) Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank Fuel Tank Some With Integrated Oil Seperator and Heater 130 A / 6,5 kW Tanks Fuel Tank Sol L Aluminium	Automated Transmission / Ratios (1.gear - 9 gear)					
Power Assisted Single CircuitChassis7 mm with ReinforcementChassis Thickness7 mm with ReinforcementChassis Strength355 MPaSuspension (Front/Rear)Parabolic Leaf Spring / Compensating Arm Mechanical SuspensionAxleStandard Single ReductionAxle Ratio4,63Tyres (Front/Rear)315/80 R 22,5Wheel Rim22,5 x 9 SteelBraking SystemBrakes (Front/Rear) (Ø.mm x mm. Length)430 x 45 - Disc BrakeBraking SystemDual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and HeaterEngine Brake Powermax. 220 kW (Engine Level)Electrical System225 AhBatterry225 AhAlternator / Starter Motor130 A / 6,5 kWTanks350 L Aluminium	Steering					
Chassis Thickness 7 mm with Reinforcement Chassis Strength 355 MPa Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction Axle Ratio 4,63 Tyres (Front/Rear) 315/80 R 22,5 Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max. 220 kW (Engine Level) Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium		Power Assisted Single Circuit				
Chassis Strength Suspension (Front/Rear) Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction Axle Ratio 4,63 Tyres (Front/Rear) 315/80 R 22,5 Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) Brakes (Front/Rear) (Ø.mm x mm. Length) Brakes (Front/Rear) (Ø.mm x mm. Length) Brakes Power Brake Po	Chassis					
Suspension (Front/Rear) Axle Axle Axle Standard Single Reduction Axle Ratio 4,63 Tyres (Front/Rear) Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power Electrical System Battery Atternator / Starter Motor Tanks Fuel Tank Parabolic Leaf Spring / Compensating Arm Mechanical Suspension Axle Standard Single Reduction 4,63 Attended System 22,5 x 9 Steel Battery 430 x 45 - Disc Brake Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater max. 220 kW (Engine Level) Electrical System 325 Ah Alternator / Starter Motor Tanks Fuel Tank 350 L Aluminium	Chassis Thickness	7 mm with Reinforcement				
Axle Standard Single Reduction Axle Ratio 4,63 Tyres (Front/Rear) 315/80 R 22,5 Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max. 220 kW (Engine Level) Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium	Chassis Strength					
Axle Standard Single Reduction Axle Ratio 4,63 Tyres (Front/Rear) 315/80 R 22,5 Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max. 220 kW (Engine Level) Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium	Suspension (Front/Rear)	Parabolic Leaf Spring / Compensating Arm Mechanical Suspension				
Axle Ratio 4,63 Tyres (Front/Rear) 315/80 R 22,5 Wheel Rim 22,5 x 9 Steel Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) 430 x 45 - Disc Brake Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power max. 220 kW (Engine Level) Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium						
Wheel Rim Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) Braking System Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power Engine Brake Power Electrical System Battery Alternator / Starter Motor Tanks Fuel Tank 22,5 x 9 Steel 22,5 x 9 Steel 22,5 x 9 Steel 330 x 45 - Disc Brake Engine Brake 430 x 45 - Disc Brake Engine Brake 320 kW (Engine Level) 130 A / 6,5 kW 350 L Aluminium	Axle Ratio					
Braking System Brakes (Front/Rear) (Ø.mm x mm. Length) Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power Engine Brake Power Electrical System Battery 225 Ah Alternator / Starter Motor Tanks Fuel Tank 350 L Aluminium	Tyres (Front/Rear)	315/80 R 22,5				
Brakes (Front/Rear) (Ø.mm x mm. Length) Brakes (Front/Rear) (Ø.mm x mm. Length) Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power Electrical System Battery 225 Ah Alternator / Starter Motor Tanks Fuel Tank 350 L Aluminium	Wheel Rim	22,5 x 9 Steel				
Brakes (Front/Rear) (Ø.mm x mm. Length) Brakes (Front/Rear) (Ø.mm x mm. Length) Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power Electrical System Battery 225 Ah Alternator / Starter Motor Tanks Fuel Tank 350 L Aluminium	Braking System					
Braking System Dual Brake Circuit - Air Processing Unit With Integrated Oil Seperator and Heater Engine Brake Power Engine Brake Power Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium		430 x 45 - Disc Brake				
Engine Brake Power max. 220 kW (Engine Level) Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium	Braking System					
Electrical System Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium						
Battery 225 Ah Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium	-					
Alternator / Starter Motor 130 A / 6,5 kW Tanks Fuel Tank 350 L Aluminium		225 Ah				
Tanks Fuel Tank 350 L Aluminium						
Fuel Tank 350 L Aluminium		.55 6,6				
		3501 Aluminium				
	SCR Tank	55 L				



Dimensions (mm)	
Front Overhang	1500
Wheelbase	4250
Overall Length	8840
Distance between 2 nd and 3 th wheel centers	1320
Overall Cab Length	1820
Overall Vehicle Height	3105
Overall Vehicle Width (Excluding Mirrors)	2540
Chassis Width	866
Rear Overhang	1770
Useful Chassis Length	6486
Chassis Height - Front	1078
Chassis Height - Rear	1073
Ground Clearance - Front	304
Ground Clearance - Rear	239
Turning Radius	9350

Weights (kg)	1. Axle	2. Axle	3. Axle	Total
Technically Permissible Weights	7100	12000	8700	26000
Kerb Weight	4587	2015	1353	7955
Payload	2513	9985	7347	18045
GVM (Legal)	7100	11500	8700	25000

STANDARD EQUIPMENT

- Air Conditioner
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- Cruise Control
- Differential Lock
- Disc Brake
- Engine Brake
- Electronic Brake System (EBS) and
- Anti-Lock Brake System (ABS)
- Electronic Stability Control (ESP)
- Hill Launch Assist
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Rake and Reach Adjustable Steering Column
- Electrically Operated Headlight Leveling
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Brake Lining Wear Sensor
- Immobilizer
- Auto Light Sensor
- Home Safe Light
- Approach Light
- Front Fog Lamps
- Digital Tachograph
- Spare Wheel
- Tag Axle Lifting (Auto Drop Function)
- DAB Radio***
- Advanced Driver-Assistance Systems (Cybersecurity Improvements, Rear View Camera, Moving-off Information System, Blind Spot Information System, Tire Pressure Monitoring System, Emergency Stop Signal, Alcohol Interlock Facilitation, Traffic Sign Recognition, Driver Alert System, Lane Keeping Alert, Pre-Collision Assist)

OPTIONAL EQUIPMENT

- Residual Collection Pack
- Firefighter Pack
- Tranmission Driven PTO & Interior Control Unit
- Engine Driven PTO & Interior Control Unit **
- ADR
- Cold Climate Pack
- Auxiliary Cabin Heater (Wet Type)
- Power Cab Tilting
- Metallic Paint / Special Colors
- 4750 mm Wheelbase Option
- Vertical Exhaust *
- Short Bumper *
- Dual Passenger Seat
- Low Liner Pack with 315/60 Tyre and 4,11 Axle Ratio
- O2 -up to 3,5T Towing Capability
- O3 10T Towing Capability with 4,89 FDR
- 8T Front Axle Technical Capacity (Available only with 315/80 Tyres)
- Manually Operated Sunroof
- Less Spare Tire
- Rain Sensor
- Technology Pack (Auto High-Beam Headlamps & Pre-Collision Assist for Pedestrian)

^{*} Available for Residual Collection Pack Only.

^{**} Available for Residual Collection Pack & Fire Fighters.

^{***} DAB Radio can be standard or optional according to the market.