

FORD TRUCKS 4142D EURO6





Basic Features	
Vehicle Type	Tipper
Axle	8x4
Emission	Euro 6
Cabin Type	Day Cab
Wheelbase (mm)	5100

Lingine	
Type	Ecotorq 12,7 litre
Displacement (cc)	12740
Diameter x Stroke	130 mm x 160 mm
Power	420 PS (308,9 kW) / 1800 rpm
Torque	2150 Nm / 1000-1300 rpm
Compression Ratio	17 +/- 0,5 : 1
Oil Filling Volume	50 L

Iransiii	IISSION
Clutch	

Coolant Volume

2 x 400 mmTwin Clutch Manuel Transmission / Ratios (1. gear - 16. gear) ZF 16S 2530 (13,805-0,836) Automated Transmission / Ratios (1. gear - 16. gear) Ecotorq 16S 2600 OD (14,107 - 0,823)

Steering

Electro-Hydraulic Power-Assisted Steering System(EHPAS)

57 L (77 L with Retarder)

Chassis						
Chassis Thickness	10 mm with Reinforcement					
Chassis Strength	500 MPa					
Suspension (Front / Rear)	90 mm Parabolic Leaf Springs / Reinforced Parabolic Suspension					
Axle	Hub Reduction					
Axle Ratio (Manual / Automatic)	4,87 / 4,08					
Tyres	315/80 R 22,5					
Wheel Rim	22,5 x 9 Steel					

Braking System

Brakes (Ø mm x mm Length)	410 x 200, Z-Cam Drum Brake System				
Braking System	Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater				
Engine Brake Power	max. 320 kW (Engine Level)				
Retarder Power	max. 450 kW / Continuous 160 kW				
Electrical System					
Battery	225 Ah				

Licetiie	ut Dyst	S
Battery		

Alternator / Starter Motor	130 A / 6,5 kW
Tanks	
Fuel Tank	315 L Steel
SCR Tank	55 L



Dimensions (mm)					
Front Overhang			1500		
Wheelbase			5100		
Overall Length			8890		
Distance Between 1st and 2nd Wheel Centers			2050		
Distance Between 2 nd and 3 th Wheel Centers			3050		
Distance Between 3th and 4th Wheel Centers			1350		
Overall Cab Length			1820		
Total Vehicle Height			3245		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			940		
Useful Chassis Length			6490		
Chassis Height - Front			1185		
Chassis Height - Rear			1186		
Ground Clearance - Front			380		
Ground Clearance - Rear			296		
Turning Radius			10640		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	8000	8000	13400	13400	41900
Kerb Weight	3826	3765	2046	2045	11682

4235

8000

4174

8000

STAND	ARD	EQUIP	MENT

- Manuel Air conditioner
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- 4 Points Independent Cab Suspension for Day Cab
- Transmission Offset (Double gear) PTO without Flange & Interior Control Unit
- Cruise Control
- Drum Brake

Payload

GVM (Legal)

- Engine Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Switchable Air Compressor for Improved Fuel Economy
- Lumbar Support
- Anti-Lock Brake System (ABS)
- Brake Lining Wear Indicator
- Immobilizer
- Home Safe Light
- Approach Light
- Differential Lock
- Digital Tachograph
- Front Towing Hooks (Double Hook)
- Short Bumper
- DAB Radio***
- Automatic Traction Control (ATC)
- Electronic Brake System (EBS) and Electronic Stability Control (ESP)
- Advanced Driver-Assistance Systems (Cybersecurity Improvements, Rear View Camera, Moving-off Information System, Blind Spot Information System, Tire Pressure Monitoring System, Emergency Stop Signal, Alcohol Interlock Facilitation, Traffic Sign Recognition, Driver Alert System, Lane Keeping Alert)

OPTIONAL EQUIPMENT

 Automated Transmission (with Normal Mode, Off-Road Mode, Rocking Mode)

11355

9500

30218

32000

• Engine Driven PTO & Interior Control Unit

11354

9500

- Transmission Driven PTO Options & Interior Control Unit
- Auxiliary Cabin Heater (Wet Type)
- Cold Pack with Wet Type Cab Heater*
- Power Cab Tilting
- Rear Window **
- 4750 mm Wheelbase Version
- Double Passenger Seat
- Extra Heavy Duty Pack (Available With 13R 22,5 Tyre)
- O2 up to 3,5T towing capability
- O3 up to 10T towing capability
- O4 more than 10T towing capability
- · Manually Operated Sunroof
- Front Vehicle Antiroll Bar
- Oil Pan Protection
- Multileaf Spring Front Suspension
- Lateral Protection
- Reinforced Wheel Rim
- Less Spare Tire
- Rear Towing Hook Option
- Twin PTO (high ratio) / Twin PTO (low ratio)****
- Retarder
- Rain Sensor
- Led Headlamps

* Not Available with 4750 mm Wheelbase Version. ** Not Available with Low Roof Sleeper Cab Version.

*** DAB Radio can be standard or optional according to the market.

****Only available with Automated Transmission.