

FORD TRUCKS 4142M EURO6





Basic Features	
Vehicle Type	Mixer
Axle	8x4
Emission	Euro 6
Cabin Type	Day Cab
Wheelbase (mm)	5100

 Engine

 Type
 Ecotorq 12,7 liters

 Displacement (cc)
 12740

 Bore x Stroke
 130 mm x 160 mm

 Power
 420 PS (308,9 kW) / 1800 rpm

 Torque
 2150 Nm / 1000-1300 rpm

 Compression Ratio
 17 +/- 0,5 : 1

 Oil Filling Volume
 50 L

Coolant Volume 57 L (77 L with Retarder)

Transmission

Clutch 430 mm Single Disc

Manuel Transmission / Ratios (1. gear - 16. gear) ZF 16S 2530 (13,805-0,836)

Automated Transmission / Ratios (1. gear - 16. gear) Ecotorq 16S 2600 OD AMT (14,107 - 0,823)

Steering

Electro-Hydraulic Power-Assisted Steering System (EHPAS)

Chassis

Chassis Thickness

Chassis Strength

Suspension (Front / Rear)

Axle

Axle Ratio (Manual / Automatic)

Tyres

Wheel Rim

10 mm with Local Reinforcement

500 MPa

90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension

Hub Reduction

4,08 / 3,57

Tyres

315/80 R 22,5

Wheel Rim

Braking System

Brakes (Ø mm x mm Length)
430 x 45 - Disc Brakes

Braking System
Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater
Engine Brake Power
max. 320 kW (Engine Level)

Retarder Power max. 450 kW / continuous 160 kW

Electrical System

 Battery
 225 Ah

 Alternator / Starter Motor
 130 A / 6, 5 kW

Tanks

 Fuel Tank
 315 L Steel

 SCR Tank
 55 L



Dimensions (mm)					
Front Overhang			1500		
Wheelbase			5100		
Overall Length			8890		
Distance Between 1st and 2nd Wheel Centers			2050		
Distance Between 2 nd and 3 th Wheel Centers			3050		
Distance Between 3th and 4th Wheel Centers			1350		
Overall Cab Length			1820		
Overall Vehicle Height			3200		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			940		
Useful Chassis Length			6494		
Chassis Height - Front			1185		
Chassis Height - Rear			1186		
Ground Clearance - Front			380		
Ground Clearance - Rear			296		
Turning Radius			10640		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	8000	8000	13400	13400	41900
Kerb Weight	3676	3848	1913	1913	11350

4354

8000

STANDARD EQUIPMENT

- Manuel Air conditioner
- Multimedia System with 9" Touch Screen & Navigation (Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- 4 Points Independent Cab Suspension for Day Cab
- Engine Driven PTO & Interior Control Unit
- Cruise Control
- Engine Brake
- Disc Brake

Payload

GVM (Legal)

- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- · Heated and Air Suspended Driver Seat
- Lumbar Support
- Anti-lock Brake System (ABS)
- Continuous Wear Sensor
- Immobilizer
- · Home Safe
- · Approach Lights
- Differential Lock
- Digital Tachograph
- Rear Window **
- Front Towing Hooks (Double Hook)
- Short Bumper
- DAB Radio***
- Electronic Brake System (EBS) and Electronic Stability Control (ESP)
- Automatic Traction Control (ATC)
- Advanced Driver-Assistance Systems (Cybersecurity Improvements, Rear View Camera, Moving-off Information System, Blind Spot Information System, Tire Pressure Monitoring System, Emergency Stop Signal, Alcohol Interlock Facilitation, Traffic Sign Recognition, Driver Alert System, Lane Keeping Alert)

OPTIONAL EQUIPMENT

Retarder

4152

8000

- ADR Pack
- Wet Type Cab Heater
- Auxiliary Cabin Heater (Wet Type)

11487

9500

- Cold Pack with Dry & Wet Type Cab Heater and 225 Ah Battery*
- Switchable Air Compressor for Improved Fuel Economy

11487

9500

30550

32000

- Transmission Driven PTO Options & Interior Control Unit
- Rubber Suspension (28T)**
- Front and Rear Vehicle Antiroll Bars
- Dual Passenger Seat*
- Lateral Protection
- Manually Operated Sunroof
- Less Spare Tire
- Rear Towing Hook
- Twin PTO (high ratio) / Twin PTO (low ratio)****
- Led Headlamps

* Not available with Low Roof Sleeper cab version.

** 241 kg lighter compared to standard suspension vehicle.

*** DAB Radio can be standard or optional according to the market.