FORD TRUCKS 4142P EURO6



Basic Features					
Vehicle Type	Concrete Pump				
Axle	8x4				
Emission	Euro 6				
Cabin Type	Day Cab				
Wheelbase (mm)	5100				
Engine					
Туре	Ecotorq 12.7 lt				
Displacement (cc)	12740				
Bore x Stroke	130 mm x 160 mm				
Power	420 PS (308,9 kW) / 1800 RPM				
Torque	2150 Nm / 1000-1300 RPM				
Compression Ratio	17 +/- 0,5 : 1				
Oil Filling Volume	50 L				
Coolant Volume	57 L				
Transmission					
Clutch	430 mm Single Disc				
Manuel Transmission / Ratios (1. gear - 16. gear)	ZF 16S 2530 (13,805-0,836)				
Steering					
	Electro-Hydraulic Power-Assisted Steering System (EHPAS)				
Chassis					
Chassis Chassis Thickness	10 mm with Local Reinforcement				
	10 mm with Local Reinforcement 500 MPa				
Chassis Thickness Chassis Strength					
Chassis Thickness	500 MPa				
Chassis Thickness Chassis Strength Suspension (Front / Rear)	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle Axle Ratio Tyres	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle Axle Ratio Tyres Wheel Rim	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 315/80 R 22,5				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle Axle Ratio Tyres	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 315/80 R 22,5				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle Axle Ratio Tyres Wheel Rim Braking System	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 315/80 R 22,5 22,5 x 9 Steel				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle Axle Ratio Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 315/80 R 22,5 22,5 x 9 Steel 410 x 200, Z-Cam Drum Brake System Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle Axle Ratio Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System Engine Brake Power	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 315/80 R 22,5 22,5 x 9 Steel 410 x 200, Z-Cam Drum Brake System				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle Axle Ratio Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System Engine Brake Power Electrical System	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 315/80 R 22,5 22,5 x 9 Steel 410 x 200, Z-Cam Drum Brake System Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level)				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle Axle Ratio Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System Engine Brake Power Electrical System Battery	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 315/80 R 22,5 22,5 x 9 Steel 410 x 200, Z-Cam Drum Brake System Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level) 225 Ah				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle Axle Ratio Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System Engine Brake Power Electrical System Battery Alternator / Starter Motor	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 315/80 R 22,5 22,5 x 9 Steel 410 x 200, Z-Cam Drum Brake System Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level)				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle Axle Ratio Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System Engine Brake Power Electrical System Battery Alternator / Starter Motor Tanks	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 315/80 R 22,5 22,5 x 9 Steel 410 x 200, Z-Cam Drum Brake System Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level) 225 Ah 130 A / 6,5 kW				
Chassis Thickness Chassis Strength Suspension (Front / Rear) Axle Axle Ratio Tyres Wheel Rim Braking System Brakes (Ø mm x mm Length) Braking System Engine Brake Power Electrical System Battery Alternator / Starter Motor	500 MPa 90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension Hub Reduction 4,08 315/80 R 22,5 22,5 x 9 Steel 410 x 200, Z-Cam Drum Brake System Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 320 kW (Engine Level) 225 Ah				



Sharing the load

Dimensions (mm)					
Front Overhang			1500		
Wheelbase			5100		
Overall Length			9850		
Distance Between 1 st and 2 nd Wheel Centers			2050		
Distance Between 2 nd and 3 th Wheel Centers			3050		
Distance Between 3 th and 4 th Wheel Centers			1350		
Overall Cab Length			1820		
Total Vehicle Height			3195		
Overall Vehicle Width (Excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			1900		
Useful Chassis Length			7440		
Chassis Height - Front			1146		
Chassis Height - Rear			299		
Ground Clearance - Front			282		
Ground Clearance - Rear			297		
Turning Radius			11930		
Weights (kg)	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	8000	8000	13400	13400	41900
Kerb Weight	3894	3900	2090	2090	11973
Payload	4106	4100	11310	11310	29927
GVM (Legal)	8000	8000	9500	9500	32000

STANDARD EQUIPMENT

- Manuel Air Conditioner
- Multimedia System with 9" Touch Screen & Navigation(Radio, Bluetooth, USB (A Type - C Type), Apple CarPlay, Android Auto, Remote Control)
- 4 Points Independent Cab Suspension for Day Cab
- Cruise Control
- Engine Brake
- Drum Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Front and Rear Vehicle Antiroll Bars
- Anti-Lock Brake System (ABS)
- Brake Lining Wear Indicator
- Immobilizer
- Home Safe Light
- Approach Light
- Differential Lock
- Digital Tachograph
 Switchable Air Comp
- Switchable Air Compressor for Improved Fuel Economy
- Rear Window
- Short Bumper
- Front Towing Hooks (Double Hook)
- DAB Radio*
- Electronic Brake System (EBS) and Electronic Stability Control (ESP)
- Automatic Traction Control (ATC)
- Advanced Driver-Assistance Systems (Cybersecurity Improvements, Rear View Camera, Moving-off Information System, Blind Spot Information System, Tire Pressure Monitoring System, Emergency Stop Signal, Alcohol Interlock Facilitation, Traffic Sign Recognition, Driver Alert System, Lane Keeping Alert)

OPTIONAL EQUIPMENT

ADR Pack

- Auxiliary Cabin Heater (Wet Type)
 Cold Pack with Wet Type Cab Heater and
- 225 Ah Battery • Power Cab Tilting
- Engine Driven PTO & Interior Control Unit
- Dual Passenger Seat
- Lateral Protection
- Manually Operated Sunroof
- Less Spare Tire
- Led Headlamps

This leaflet includes products designed for Ford vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications. Selection of any optional accessories might cause differences from these specifications.