


FORD TRUCKS 3233M EURO6





Basic Features			
Vehicle Type	Light Mixer		
Axle	8x4		
Emission	Euro 6		
Cabin Type	Day Cab		
Wheelbase (mm)	5100		
Engine			
Туре	Ecotorq 9 litre		
Displacement [cc]	8974		
Diameter x Stroke	Euro 6 Day Cab 5100 Ecotorq 9 litre		
Power	330 PS (243 kW) / 1900 d/d		
Torque	1300 Nm / 1200-1700 d/d		
Compression Ratio	17,6 : 1		
Oil Filling Volume [l]	30 L		
Coolant volume [l]	35 L		
Transmission			
Clutch	430mm Single Disc		
Manuel Transmission / ratios (1.gear- 16. gear)	ZF 16S 1630 (13,805-0,836)		
Steering			
	Power Assisted Single Circuit		

Steering			
Chassis			
Chassis thickness [mm]			
Chassis Strength [MPa]			
Suspension (Rear/Front)			
Axle			
	Chassis Chassis thickness [mm] Chassis Strength [MPa] Suspension (Rear/Front)	Chassis Chassis thickness [mm] Chassis Strength [MPa] Suspension (Rear/Front)	Chassis Chassis thickness [mm] Chassis Strength [MPa] Suspension (Rear/Front)

Cildasis					
Chassis thickness [mm]	10mm with Reinforcement				
Chassis Strength [MPa]	500 MPa				
Suspension (Rear/Front)	90 mm Parabolic Leaf Springs / Rubber Suspension (24T)				
Axle	Hub Reduction				
Axle Ratio	5,24				
Tyres	315/80 R 22,5				
Wheel Rim	22,5 x 9 Steel				
Braking System					

Brakes (front/rear) (Ø.mm x mm. length)	
Braking System	
Engine Brake Power	

430 x 45 - Disc Brakes

Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater max. 220 kW (Engine Level)

Electrical System	
Battery	24 V, 2 x 12 V 150 Ah
Alternator / Starter Motor	130 A / 6.5 kW
Tanks	

250 L Steel







Dimensions [mm]					
Front Overhang			1500	100	
Wheelbase			5100		
Overall Length			8890		
Distance Between 1st and 2nd Wheel Centers			2050		
Distance between 2nd and 3th wheel centers			3050		
Distance Between 3th and 4th Wheel Centers			1350		
Overall Cab Length			1820		
Overall Vehicle Height			3198		
Overall Vehicle Width (excluding Mirrors)			2540		
Chassis Width			770		
Rear Overhang			940		
Useful Chassis Length			6535		
Chassis Height-Front			225		
Chassis Height-Rear			285		
Ground Clearance-Front			495		
Ground Clearance-Rear			282		
Turning Radius			10640		
Weights [kg]	1. Axle	2. Axle	3. Axle	4. Axle	Total
Technically Permissible Weights	8000	8000	12000	12000	39000
Kerb Weight	3251	3282	1797	1705	10035
Payload	4749	4718	10203	10295	28965

7500

STANDARD EQUIPMENT

Air Conditioner

GVM (Legal)

- Radio/CD Player
- Engine Driven PTO & Interior Control Unit
- 4 Point Independent Cab Suspension for Day Cab
- Cruise Control
- Disc Brake
- Engine Brake
- Electrically Operated Windows
- Electrically Operated and Heated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat
- Lumbar Support
- Manually Operated Sunroof
- Front and Rear Vehicle Antiroll Bars
- Anti-lock Brake System (ABS)
- Brake Lining Wear Sensor
- Immobilizer
- Single Key with Remote Control and Central Locking
- Home Safe
- Approach Lights
- Differential Lock
- Digital Tachograph
- Rear Window **

OPTIONAL EQUIPMENT

- Low Roof Sleeper Cab
- Wet Type Cab Heater
- Cold Pack with Wet Type Cab Heater
- Cold Pack with Dry & Wet Type Cab Heater *

9500

9500

32000

• Power Cab Tilting

7500

- Tranmission Driven PTO Options & Interior Control Unit
- Automatic Traction Control (ATC)

This leaflet includes products designed for Ford vehicles. It provides information about the current technical specifications and the standard or optional accessories available as of the date it was issued. Features of standard and optional accessories of the vehicles may be changed from time to time. For this reason, please consult our Authorized Dealers to obtain updated and accurate information on the features of the vehicle you wish to buy. For the aforementioned reason, this leaflet does not constitute an assurance as to the specifications listed herein. The images used in this leaflet may be different from the vehicles on sale. The technical specifications provided herein are for standard vehicles.

Selection of any optional accessories might cause differences from these specifications.

^{*}Only available with Low Roof Sleeper cab version.

^{**} Not available with Low Roof Sleeper cab version.